



The Hallmark of Oil Maintenance

HYDRAULIC FILTRATION UNITS

With Electric Pump Motors

Electric pump motor units are designed for a wide range of special applications. These include, around-the-clock filtration, continuous filters of bulk storage tanks, and machinery or lubrication systems that don't have high pressures to tap from the main lines.



SUITED FOR:



around-the-clock filtration,
filtration during machine
downtime or uptime,
filtration when main system
pressure is not an option,
bulk storage tanks



APPLICATION:

wide range of reservoir
capacities and special
applications

SPECIFICATIONS FOR HYDRAULIC FILTRATION UNITS



overall dimensions	18" x 9" x 18"	18" x 9" x 18"
net weight	55 lbs.	59 lbs.
dirt holding capacity	1 lb.	1.25 lbs.
water removing capacity	20 ozs.	24 ozs.
quantity of oil in machine	Up to 325 gal.	Up to 450 gal.
oil (ISO) cleanliness	16/14/11 or better	16/14/11 or better
filtering accuracy	0.1 micron	0.1 micron
flow rate	0.80 GPM	0.80 GPM
volts	110/220-230	110/220-230
housing burst strength	250-400 PSI	250-400 PSI
normal viscosity	9-180 cSt @ 40°C	9-180 cSt @ 40°C
inlet diameter	3/8" pipe nipple	3/8" pipe nipple
outlet diameter	3/8" pipe nipple	3/8" pipe nipple
safety valve check pressure	65 PSI	65 PSI



OILSERVE

บริษัท ออยเซอร์ฟ จำกัด
OILSERVE CO., LTD.

9 ซอยทวีวัฒนา 25 แยก 7 แขวงทวีวัฒนา เขตทวีวัฒนา กรุงเทพฯ 10170
9 Soi Thawi Watthana 25 Yeak 7, Thawi Watthana, Thawi Watthana, Bangkok 10170
Tel: (+662) 441 9247 Fax : (+662) 441 9248 TAX ID : 0105553015358
E-mail : sales@oilserve-thai.com, oilserveco@gmail.com, www.oilserve-thai.com

www.filtroil.com