



The Hallmark of Oil Maintenance

## HYDRAULIC FILTRATION UNITS For Field Retro-fit Installation

Filtroil's dedicated by-pass filtration systems help you preserve and maintain your hydraulic system by filtering efficiently down to 0.1 micron. This filtration accuracy will allow you to prevent failures on pumps, servo valves, proportional valves, and cylinders.

Filtroil will maintain hydraulic oil cleanliness 2 to 5 grades cleaner than brand new oil, dramatically extending the life of the oil while removing moisture. All units include complete retrofit installation kits.



### SUITED FOR:


hydraulic systems with pumps, servo valves, proportional valves, cartridge valves, and cylinders



### APPLICATION:

dedicated units designed for field retro-fit installation for stationary or mobile hydraulic equipment

# SPECIFICATIONS FOR HYDRAULIC FILTRATION UNITS



	<b>BU-30</b>	<b>BU-50</b>	<b>BU-100</b>	<b>BU-200</b>	<b>BU-400</b>
<b>overall dimensions</b>	5.3" x 12"	7.2" x 11.5"	8.9" x 12.2"	9.4" x 12.2"	20" w x 10.5" d x 17.5" h
<b>net weight</b>	13 lbs.	16 lbs.	21 lbs.	25 lbs.	46 lbs.
<b>quantity of oil in machine</b>	up to 50 gal.	up to 125 gal.	up to 325 gal.	up to 450 gal.	up to 1000 gal.
<b>dirt holding capacity</b>	.6 lbs.	.75 lbs.	1 lbs.	1.25 lbs.	2.5 lbs.
<b>water holding capacity</b>	12 ozs.	15 ozs.	20 ozs.	24 ozs.	48 ozs.
<b>oil (ISO) cleanliness</b>	16/14/11 or better	16/14/11 or better	16/14/11 or better	16/14/11 or better	16/14/11 or better
<b>filtering accuracy</b>	0.1 micron	0.1 micron	0.1 micron	0.1 micron	0.1 micron
<b>flow rate</b>	.30 GPM	.30 GPM	.50 GPM	.65 GPM	1.20 GPM
<b>min./max. pressure at flow control valve</b>	200/5,000 PSI	200/5,000 PSI	200/5,000 PSI	200/5,000 PSI	200/5,000 PSI
<b>housing burst strength</b>	250-400 PSI	250-400 PSI	250-400 PSI	250-400 PSI	250-400 PSI
<b>normal viscosity</b>	9-180 cSt @ 40°C	9-180 cSt @ 40°C	9-180 cSt @ 40°C	9-180 cSt @ 40°C	9-180 cSt @ 40°C
<b>inlet diameter</b>	SAE-4 (7/16-20) O-Ring	SAE-4 (7/16-20) O-Ring	SAE-4 (7/16-20) O-Ring	SAE-4 (7/16-20) O-Ring	SAE-6(9/16-18) O-Ring
<b>outlet diameter</b>	SAE-6 (9/16-18) O-Ring	SAE-6 (9/16-18) O-Ring	SAE-6 (9/16-18) O-Ring	SAE-6 (9/16-18) O-Ring	SAE-8 (1/2-20) O-Ring
<b>safety valve pressure</b>	65-70 PSI	65-70 PSI	65-70 PSI	65-70 PSI	65-70 PSI
<b>replacement element</b>	30 E 4.0" x 4.5"	50 E 5.6" x 4.5"	100 E 7.4" x 4.5"	200 E 7.8" x 4.5"	(2) 200 E 7.8" x 4.5"
<b>replacement gasket sets</b>	30 PS	50 PS	100 PS	200 PS	(2) 200 PS

For more information, contact:

**OILSERVE**

บริษัท ออยเซอร์ฟ จำกัด  
**OILSERVE CO., LTD.**

9 ซอยทวีวัฒนา 25 แยก 7 แขวงทวีวัฒนา เขตทวีวัฒนา กรุงเทพฯ 10170  
9 Soi Thawi Watthana 25 Yeak 7, Thawi Watthana, Thawi Watthana, Bangkok 10170  
Tel: (+662) 441 9247 Fax: (+662) 441 9248 TAX ID: 0105553015358  
E-mail: sales@oilservevethai.com, oilserveco@gmail.com, www.oilservevethai.com

